

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Issue date: 14-8-2012 Revision date: 12-11-2019 Supersedes: 15-9-2017 Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Product name	: 43900 - FORM OIL 10
Product code	: 43900
Type of product	: Lubricant
Product group	: Industrial

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category

: Industrial use, Professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

77 Lubricants 1761 JA - The Netherlands T +31 (0)78 6527652 technical@77lubricants.nl - www.77lubricants.nl

1.4. Emergency telephone number

Emergency number

: +31 (0)78 6527652 Monday to Friday: 09:00 - 16:00 (CET)

SECTION 2: Hazards identification	
2.1. Classification of the substance or mix	ture
Classification according to Regulation (EC) No. Not classified	1272/2008 [CLP]
Adverse physicochemical, human health and en May be fatal if swallowed and enters airways.	vironmental effects
2.2. Label elements	
Labelling according to Regulation (EC) No. 1272	2/2008 [CLP]
EUH-statements	 EUH208 - Contains Calcium bis(dinonylnaphthalenesulphonate)(57855-77-3). May produce an allergic reaction. EUH210 - Safety data sheet available on request.
2.3. Other hazards	
Other hazards not contributing to the classification	: Flammable liquids. Prolonged or repeated contact may cause dermatitis by loss of natural skin fats. Spills of this product present a serious slipping hazard.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] substance with a Community workplace exposure limit (Note L)	(CAS-No.) 64742-65-0 (EC-No.) 265-169-7 (EC Index-No.) 649-474-00-6 (REACH-no) 01-2119471299-27	10 – 25	Not classified

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general First-aid measures after inhalation First-aid measures after skin contact First-aid measures after eye contact First-aid measures after ingestion	 Call a physician immediately. Remove person to fresh air and keep comfortable for breathing. Wash skin with plenty of water. Rinse eyes with water as a precaution. Do not induce vomiting. Call a physician immediately.
4.2. Most important symptoms and ef	fects, both acute and delayed
Symptoms/effects after inhalation Symptoms/effects after skin contact Symptoms/effects after eye contact Symptoms/effects after ingestion	 After adequate first aid, no further treatment is required unless symptoms reappear. After adequate first aid, no further treatment is required unless symptoms reappear. After adequate first aid, no further treatment is required unless symptoms reappear. After adequate first aid, no further treatment is required unless symptoms reappear. After adequate first aid, no further treatment is required unless symptoms reappear.

4.3. Indication of any immediate medical attention and special treatment needed

Ingestion of large quantities: immediately to hospital. Obtain medical assistance. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.Do not use a water jet since it may cause the fire to spread.
5.2. Special hazards arising from the subs	tance or mixture
Hazardous decomposition products in case of fire	: Toxic fumes may be released.
5.3. Advice for firefighters	
Precautionary measures fire Protection during firefighting	 Evacuate area. Stop leak if safe to do so. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 6: Accidental release me	easures
6.1. Personal precautions, protective of	equipment and emergency procedures
General measures	: Eliminate every possible source of ignition.
6.1.1. For non-emergency personnel	
Protective equipment Emergency procedures	Wear suitable protective clothing and eye/face protection.Ventilate spillage area.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Avoid release to the environment.	
6.3. Methods and material for contain	ment and cleaning up
For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up Other information	Take up liquid spill into absorbent material.Dispose of materials or solid residues at an authorized site.
6.4. Reference to other sections	

For further information refer to section 13.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed Precautions for safe handling Handling temperature Hygiene measures	 No open flames, no sparks, and no smoking. Do not pierce or burn, even after use. Ensure good ventilation of the work station. Wear personal protective equipment. 5 - 40 °C Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, inclu	ding any incompatibilities
Storage conditions Storage temperature Storage area Special rules on packaging	 Store locked up. Store in a well-ventilated place. Keep cool. 45 °C Store away from heat. Store in a well-ventilated place. Keep only in original container. Store in a closed container.
7.3. Specific end use(s)	

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0) EU - Occupational Exposure Limits

IOELV TWA (mg/m ³)	5 mg/m³
IOELV STEL (mg/m ³)	10 mg/m³

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Bulgaria - Occupational Exposure Limits	
OEL TWA (mg/m³)	5 mg/m³
OEL STEL (mg/m³)	10 mg/m³
Croatia - Occupational Exposure Limits	
GVI (granična vrijednost izloženosti) (mg/m³)	5 mg/m³
KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	10 mg/m³
Czech Republic - Occupational Exposure Limits	·
Expoziční limity (PEL) (mg/m ³)	5 mg/m³
Expoziční limity (NPK-P) (mg/m ³)	10 mg/m³
Denmark - Occupational Exposure Limits	·
Grænsevædi (8 timer) (mg/m³)	1 mg/m³
Netherlands - Occupational Exposure Limits	·
Grenswaarde TGG 8H (mg/m³)	5 mg/m³
8.2. Exposure controls	·

Appropriate engineering controls:

Use adequate ventilation to keep oil mist below applicable standard. Use splash goggles when eye contact due to splashing is possible. Ocular shower with suitable liquid.

Personal protective equipment:

Gloves. Safety glasses. Protective clothing. Avoid all unnecessary exposure.

Materials for protective clothing:

Wear suitable protective clothing

Hand protection:

Breakthrough time : refer to the recommendations of the supplier

T	уре	Material	Permeation	Thickness (mm)	Penetration	Standard
		Nitrile rubber (NBR), Neoprene rubber (HNBR)	5 (> 240 minutes)	0.7	3 (> 0.65)	EN ISO 374
		Polyvinylchloride (PVC)	2 (> 30 minutes)	0.4	3 (> 0.65)	EN ISO 374

Eye protection:

Chemical goggles or safety glasses. Use splash goggles when eye contact due to splashing is possible. EN 166

Skin and body protection:

Avoid prolonged and repeated contact with skin. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn

Respiratory protection:

Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Particle filter. EN 143

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light yellow.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -24 °C
Boiling point	: No data available
Flash point	: > 140 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 852,1 kg/m³ @15°C
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 10 mm²/s @40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

Minimum ignition energy

: ≈

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information		
11.1. Information on toxicologica	leffects	
Acute toxicity (oral) Acute toxicity (dermal)	: Not classified : Not classified	
Acute toxicity (inhalation)	: Not classified	

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5,53 mg/l/4h
Skin corrosion/irritation :	Not classified
	Not classified
, .	Not classified
	Not classified
Carcinogenicity :	Not classified
Reproductive toxicity :	Not classified
STOT-single exposure :	Not classified
STOT-repeated exposure :	Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight

Aspiration hazard : Not classified		Not classified
	43900 - FORM OIL 10	
	Viscosity, kinematic	10 mm²/s @40°C

SECTION 12: Ecological information

12.1. Toxicity	
Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

hydrocarbons obtained by removal of normal	y paraffinic; Baseoil— unspecified; [A complex combination of paraffins from a petroleum fraction by solvent crystallization. It consists n numbers predominantly in the range of C20 through C50 and produces a SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)	
LC50 fish 1 100 mg/l		
EC50 Daphnia 1	10000 mg/l	
EC50 72h algae (1)	3 mg/l	
12.2. Persistence and degradability		
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)		
Persistence and degradability	Not biodegradable.	
Biodegradation	31 % 28 d OECD 301F	
12.3. Bioaccumulative potential		
hydrocarbons obtained by removal of normal	y paraffinic; Baseoil— unspecified; [A complex combination of paraffins from a petroleum fraction by solvent crystallization. It consists n numbers predominantly in the range of C20 through C50 and produces a SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)	
Bioconcentration factor (BCF REACH) 260		
Partition coefficient n-octanol/water (Log Pow)	9,2	
12.4. Mobility in soil		
No additional information available		
12.5. Results of PBT and vPvB assessment		

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number		
UN-No. (ADR) UN-No. (IMDG) UN-No. (IATA) UN-No. (ADN) UN-No. (RID)	 Not applicable Not applicable Not applicable Not applicable Not applicable 	
14.2. UN proper shipping name		
Proper Shipping Name (ADR)	: Not applicable	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Proper Shipping Name (IMDG) Proper Shipping Name (IATA) Proper Shipping Name (ADN) Proper Shipping Name (RID)	 Not applicable Not applicable Not applicable Not applicable Not applicable 	
14.3. Transport hazard class(es)		
ADR Transport hazard class(es) (ADR) IMDG Transport hazard class(es) (IMDG) IATA	Not applicable Not applicable	
Transport hazard class(es) (IATA) ADN	: Not applicable	
Transport hazard class(es) (ADN) RID Transport hazard class(es) (RID)	: Not applicable	
14.4. Packing group		
Packing group (ADR) Packing group (IMDG) Packing group (IATA) Packing group (ADN) Packing group (RID)	 Not applicable Not applicable Not applicable Not applicable Not applicable 	
14.5. Environmental hazards		
Dangerous for the environment Marine pollutant Other information	 No No No supplementary information available 	
14.6. Special precautions for user		
Overland transport No data available Transport by sea No data available Air transport No data available Inland waterway transport No data available Rail transport No data available		
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code		

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

15.1.2. National regulations

Germany	
Water hazard class (WGK)	: WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV)	: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)
Netherlands	
Ministry's list of carcinogens	: Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] is listed
Ministry's list of mutagens	: Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] is listed
NON-exhaustive list of reproductive toxins - Breastfeeding	: None of the components are listed
NON-exhaustive list of reproductive toxins - Fertility	: None of the components are listed
NON-exhaustive list of reproductive toxins - Evolution	: None of the components are listed
Denmark	
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Comments
	Supersedes	Modified	
	Revision date	Modified	
5.1	Suitable extinguishing media	Modified	
8.2	Hand protection	Modified	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
PNEC	Predicted No-Effect Concentration
РВТ	Persistent Bioaccumulative Toxic
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

Full text of H- and EUH-statements:	
EUH208	Contains Calcium bis(dinonylnaphthalenesulphonate)(57855-77-3). May produce an allergic reaction.
EUH210	Safety data sheet available on request.

SDS EU (REACH Annex II)

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness